

SLAMMER MANUFACTURING

PRESENTS

GRATEFX® U.S. PATENT # 6,706,172 B2
PRONOUNCED

"GREAT EFFECTS"

FOR USE ON

ROLL CURB, FLAT & DOME GRATE APPLICATIONS

Lightweight and easy for one person to install without removing the grate. **GrateFX®** is flush mounted, only 1/8" thick. Pedestrian safe. The Roll Curb Inlet **GrateFX®** has a Freeboard so your street won't flood and possibly cause a traffic safety concern.

GrateFX® are available from 3" to 84" round, square or rectangle. Applications include; Floor Drains, Trench Drains, Sink Drains, Paved Area Inlets (parking lots, etc.) Sidewalk Drains, Golf Course Inlets, Roll Curb Inlets, Trench Drains in Bottling Plants & Automotive Repair Facilities. Keep broken glass & those small parts out of your floor drains. The list goes on and on.

GrateFX® Perfect for highly temporary inlet protection, such as paving operations or pouring concrete. Anytime you don't want your new work falling into an inlet.

GrateFX® are constructed of 1/8th inch die cut masticated tire rubber (SBR) with a 15% open area monofilament Geotextile as a filter media. The SBR frame material can survive heavy truck and equipment traffic without being destroyed while extending the life of the filter fabric from wear and tear.



NO MORE BACKBREAKING LABOR, OR THE VERY REAL POSSIBILITY OF DROPPING THE GRATE INTO THE STRUCTURE

GrateFX® Ten Pack is only 1 ½" thick. Why fool with heavy gravel filled bags, silt fence, or straw bales?

EASE OF INSTALLATION

ONE PERSON 2 MINUTES FOR MOST SIZES



#1. APPLY BEAD OF E-6000 ADHESIVE TO GRATE



#2. POSITION **GrateFX®** ON GRATE



#4. PRESS **GrateFX®** INTO PLACE TO EVEN OUT ADHESIVE. THAT'S ALL THERE IS TO IT!



GrateFX® ROLL CURB # 5130



888-550-1999

WWW.EROSIONCONTROLSTORE.COM